

APPROVAL SPECIFICATION

PRODUCT NAME: Common Mode Choke

KOOMAG PN: KMCC2012N-2- 801T01

CUSTOMER PN:

CUSTOMER RESPONSE

<input type="checkbox"/> Approval <input type="checkbox"/> Approval with the following changes <input type="checkbox"/> Reject		
APPROVED BY	SIGNATURE	DATE

KOOMAG ENGINEERING SIGNATURE

APPROVED BY	CHECKED BY	ISSUED BY
DATE	DATE	DATE

深圳坤磁科技有限公司

SHENZHEN KOOMAG TECHNOLOGY CO., LTD


Address: B503, Building B, HuaChuangDa Headquarters Building, Bao'an 49 District, Shenzhen

KMCC2012N-2-801T01

General Description

1. This specification applies to the KMCC2012 series of Common Mode Choke. 10/100/1000MHz Ethernet Application.
2. It does not adversely affect the transmission signal of the LAN and suppresses unnecessary common mode noise.
3. Operating Temperature Range : -40 ~ +105 °C ,Storage condition : Temperature -10 ~ +40 °C, Relative humidity 40%~60%.

Appearance & Shape



Dimension (Unit:mm)



Series:	KMCC2012N-2- 801T01
A (mm)	2.0±0.2
B (mm)	1.2±0.2
C (mm)	1.20±0.2
D (mm)	0.45±0.1
E (mm)	0.50±0.1
F (mm)	0.15±0.05
G (mm)	1.40
H (mm)	1.20
I (mm)	2.6
J (mm)	0.4

Part Number

KMCC	2012	N	-	2	-	801	T	01
A	B	C		D		E	F	G

- A:Series
- B:Dimension
- C:Material
- D:Number of Lines
- E:Impedance
- F:Taping and Reel
- G:Control

Equivalent Circuit / Materials




NO.	Description	Specification
a	Upper Plate	Ferrite
b	Core	Ferrite Core
c	Termination	Ag/Ni/Sn
d	Wire	Enameled Copper Wire

Electrical Characteristics

Part No.	Common mode Impedance (Ω)	DC Resistance (Ω) max.	Test Frequency (MHz)	Rated Volt. (Vdc)max.	Rated Current (mA)max.	Withstand Volt. (Vdc)max.	IR (Ω)min.
KMCC2012N-2-801T01	800 \pm 25%	0.88	100	50	300	125	10M

Curve Frequency(MHz)



General Reflow Profile & Iron Soldering

