

APPROVAL SPECIFICATION

PRODUCT NAME: _____

KOOMAG PN: KMTTC1250 Series _____

CUSTOMER PN: _____

CUSTOMER RESPONSE

<input type="checkbox"/> Approval <input type="checkbox"/> Approval with the following changes <input type="checkbox"/> Reject		
APPROVED BY	SIGNATURE	DATE

KOOMAG ENGINEERING SIGNATURE

APPROVED BY	CHECKED BY	ISSUED BY
DATE	DATE	DATE


深圳坤磁科技有限公司
 SHENZHEN KOOMAG TECHNOLOGY CO., LTD

Address: B503, Building B, HuaChuangDa Headquarters Building, Bao'an 49 District, Shenzhen

General Description

This specification applies to the KMTC1250 Series of wire wound SMD power inductor.


Appearance & Shape



Dimension (Unit:mm)

NO	Series	A	B	C	D	E	G	H	I
1	KMTC1250	12.8 ±0.3	14±0.5	5.0 Max	2.5±0.5	3.8±0.3	7.6 Ref.	14.1 Ref.	4.5 Ref.

Part Number



A:Series name (产品品名)

B:Dimensions (产品尺寸)

C:Inductance value (电感值) 1R5: 1.5μH 220: 22μH

D:Tolerance (误差值) K: ±10%; M: ±20%; N: ±30%

Electrical Characteristics

Please refer to Item 5.


- 1). Operating temperature range (individual chip without packing): $-40^{\circ}\text{C} \sim +125^{\circ}\text{C}$.
- 2). Storage temperature range (packaging conditions): $-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$ and RH 70% (Max.).
- 3). Rating DC current: Temperature rise(ΔT) is 40°C approximately at Irms.
- 4). Saturation DC current: Inductance drop approximately 30% of L0 at Isat.

NO	Part Number	Inductance	DC Resistance		Saturation Current	Temp.Rise current	Marking
		100KHz/1.0V	Max.	Typ.	Typ.	Typ.	
	Units	(μH)	m Ω	m Ω	A	A	
1	KMTC1250-R22M	0.22 \pm 20%	0.85	0.55	50.0	28.0	R22
2	KMTC1250-R33M	0.33 \pm 20%	1.45	0.95	48.0	26.0	R33
3	KMTC1250-R47M	0.47 \pm 20%	1.6	1.1	45.0	25.0	R47
4	KMTC1250-R68M	0.68 \pm 20%	2.1	1.4	38.0	23.0	R68
5	KMTC1250-1R0M	1.00 \pm 20%	3.2	2.1	35.0	20.0	1R0
6	KMTC1250-1R5M	1.50 \pm 20%	4.0	2.6	30.0	15.0	1R5
7	KMTC1250-2R2M	2.20 \pm 20%	7.3	4.8	26.0	14.0	2R2
8	KMTC1250-3R3M	3.30 \pm 20%	9.5	6.2	24.0	13.0	3R3
9	KMTC1250-4R7M	4.70 \pm 20%	15	10.5	20.0	12.0	4R7
10	KMTC1250-6R8M	6.80 \pm 20%	25	15.8	16.0	9.0	6R8
11	KMTC1250-8R2M	8.20 \pm 20%	35	21.5	16.0	8.0	8R2
12	KMTC1250-100M	10.00 \pm 20%	42	27.5	14.0	7.0	100
13	KMTC1250-150M	15.00 \pm 20%	54	36	11.0	6.0	150
14	KMTC1250-220M	22.00 \pm 20%	68	42	9.0	5.0	220
15	KMTC1250-330M	33.00 \pm 20%	95	72	7.0	4.0	330
16	KMTC1250-470M	47.00 \pm 20%	110	85	6.0	3.0	470
17	KMTC1250-680M	68.00 \pm 20%	180	135	5.0	2.5	680
18							
19							
20							


※Design as Customer's Requested Specifications. (可按顾客的特殊需求设计)

■ Packaging(unit:mm)

1.Tape Dimensions(Unit:mm)



2.Reel



Part No.	Tape	MPQ
KMTC1250	Embossed Tape	500PCS

Soldering Condition Sproduct


Applicable soldering process to the products is refl.

1.Soldering Materials

(1)Solder:Sn-3.0Ag-0.5Cu

(2)Flux:Use rosin-based flux,but not strongly acidic flux (with xhlorine exceeding 0.2wt%).Do not use water-soluble flux.

2.Reflow Soldering Profile



3.Solderin glron

Reworking with electric soldering iron must preheating at 150°C for 1 minute is required,and do not directly touch the core with the tip of the soldering iron.The reworking soldering conditions are as follows.

- ①Temperature of soldering iron tip:350°C ;
- ② Soldering iron power output:≤30W;
- ③ Diameter of soldering iron end:≤1.0mm;
- ④Soldering time:< 3s.

